

Wired/Wireless USB2.0 MFP Print Server



With more and more MFP (Multi-Function Printer) released. PLANET is glad to introduce our new MFP print server - FPS-1010M/FPS-1010MG to you. The print servers allow users to share their MFP (Multi-Function Printer) to the wired and wireless network. Not only printer, but also scanner, fax and card reader can be shared to your network at the same time. With Windows base operation utility, users can get the MFP to print and scan your document, send a fax or reach the data from the card reader of MFP via FPS-1010M/FPS-1010MG. In addition, by using our Windows based configuration program, configuration can be completed in minutes. Equipped with the connector interface - USB2.0, the print server provides the most compatibility to the newly released MFP that built in USB 1.1 / 2.0 interface.

Not only be a MFP Server, this FPS-1010M/FPS-1010MG can also be a traditional print server. Supports TCP/IP network protocol, it allows LPR, standard TCP/IP and IPP printing methods. It can share print function in the various common network operating systems including Windows 98SE/Me/NT/2000/XP/2003, Unix, Linux and MAC OS 9.x above. Otherwise, FPS-1010M/FPS-1010MG is GDI interface supported, you can connect the GDI printer to FPS-1010M/FPS-1010MG directly.

For FPS-1010MG. This device provides a built-in high-performance wireless interface at the transfer rate up to 54Mbps for users to enjoy the convenience of wireless printing. The Print Server supports both "Ad-Hoc mode" (point-to-point wireless networks) and "Infrastructure mode" (using your existing Wireless access point). Users can make choice of the most appropriate mode for their own wireless network. Supports 64/128-bit WEP and WPA-PSK for securing wireless network connections. Since the FPS-1010MG is compliant with 802.11b/g, you can use FPS-1010MG with your existing 802.11b network as well.

KEY FEATURE

- **Support for most popular NOS**
MFP Server
Win2000 SP4, WinXP SP1 or above
- **Print Server**
Unix, Linux: TCP/IP, LPD
Windows: LPR, IPP, Standard TCP/IP printing
Apple: TCP/IP (MAC OS 9 or above)
- **Support Most MFP**
Compatible with most of the MFP on the market, such as HP, Canon, EPSON, Lexmark, SamSung and etc.
- **Auto-Sensing**
Supports 10/100Mbps Auto-Nway, Automatically Negotiates optimal mode, 10/20Mbps, 100/200Mbps
Ethernet 802.2, Ethernet 802.3, SNAP Auto-Detect.
- **Auto-MDI/MDI-X**
Auto detects the connected cable type while connecting to different LAN devices. It is capable of detecting the signal and changes its transfer/receive order on the cable automatically
- **Easy Management**
Intuitive management utility provided for Windows 95/98/2000/Me/NT/XP/Server 2003 or Web-Base Management.
- **Internet Printing Protocol (IPP) Support**
FPS-1010M/FPS-1010MG can act as IPP (Internet Printing Protocol) Server, allowing your clients, suppliers, and colleagues to operate your printers from anywhere on the Internet. Windows IPP Client software is also supplied.
- **Support GDI printer**
Supports GDI interface. FPS-1010M/FPS-1010MG can work with GDI printer and share the printer to your network.

SPECIFICATION

Product	Wired/Wireless USB2.0 MFP Print Server	
Model	FPS-1010MG	FPS-1010M
Wired Interface		
Media Interface	1 x RJ-45 UTP	
Standards	IEEE802.3, 10Base-T; IEEE802.3u, 100Base-TX; Auto-MDI/MDI-X	
Cabling	Category 5/5e or above, 2-pair	
Wireless Interface		
Frequency	2.4 to 2.4835 GHz (ISM Band)	
Standards	IEEE802.11b; IEEE802.11g	
Encryption	64/128-Bit WEP, WPA-PSK	
Data Rate	802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps	
Output Power	18 dBm (max)	
Antenna Connector	1 x RP-SMA	
General		
Printer Connector	1 * USB 2.0 (Female)	
Ethernet Connector	1 * 10/100Base-TX	
LEDs	3; LAN, ACT,WLAN	3; LAN, ACT, READY
Protocol Support	TCP/IP, HTTP, IPP, DHCP, LPR	
Power Input	5V, 2A	7.5V DC, 500mA
Cabling Type	10Base-T UTP Cat 3 or better 100Base-TX UTP Cat5 or better	
Dimension (L * W * H)	80 x 56 x 24 (mm)	75 x 56 x 23 (mm)
Weight	85g	62g
Environmental Specifications	Operating Temperature : 0~50 degree C Storage Temperature: -25 ~ 75 degree C Operating Humidity: 5~95% Storage Humidity: 5~95%	
EMI	CE, FCC Class B	

APPLICATIONS

With MFP print server connected, users can share all the functions on MFP (print, scan, fax and card reader) to the network. Besides MFP sharing, it is also support tradition printers (includes GDI interface). So it can work with your entire tradition printers easily.

When the MFP print server is assigned with a legal IP address, not only local users, but also Internet users easily connect to the attached printer through Internet with IPP printing function for satisfying the printing needs.


ORDERING INFORMATION

FPS-1010M	USB2.0 MFP Print Server
FPS-1010MG	802.11g USB MFP Print Server

PLANET Technology Corporation

11, No. 96, Min Chuan Road, Hsin tien, Taipei, Taiwan, R.O.C.
Tel: 886-2-2219-9518
Fax: 886-2-2219-9528
Email: sales@planet.com.tw
www.planet.com.tw
VoIP Gateway: vip.planet.com.tw

JALERCOM S.A. de C.V.

Av. Sor Juana Inés de la Cruz 344 1er Piso
Col. Centro, Tlalnepanitla
Edo. de Mex. C.P. 54000
Tel +52(55) 55 65 60 55
Fax +52(55) 55 65 60 55 ext. 112
mail: sales@jalercom.com
http://www.jalercom.com



PLANET reserves the right to change specifications without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright©2005 PLANET Technology Corp. All rights reserved.